

[54] IMAGE POSITION CONTROL

[76] Inventor: Harold C. Avila; 5399 Sierra Vista Ave., Riverside, Calif. 92505

[21] Appl. No.: 694,816

[22] Filed: Jan. 25, 1985

[51] Int. Cl.⁴ G09G 1/00

[52] U.S. Cl. 340/709; 340/710; 74/471 XY

[58] Field of Search 340/709, 710, 706; 178/18; 74/471 XY, 471 R, 491, 198; 338/123, 132, 133

[56] References Cited

U.S. PATENT DOCUMENTS

| | | | |
|-----------|---------|----------------|-----------|
| 1,613,994 | 1/1927 | Grose | 338/123 |
| 3,820,641 | 6/1974 | Bonst et al. | 74/471 R |
| 3,916,100 | 10/1975 | Azuma | 178/18 |
| 4,369,439 | 1/1983 | Broos | 340/710 |
| 4,543,571 | 9/1985 | Bilbrey et al. | 340/709 |
| 4,561,183 | 12/1985 | Shores | 340/710 |
| 4,562,347 | 12/1985 | Hovey et al. | 74/471 XY |

OTHER PUBLICATIONS

Leon, N., "Thumbwheel Positional Control Unit", IBM Technical Disclosure Bulletin, vol. 21, #7, Dec. 1978., pp. 3206, 3207.

Primary Examiner—John W. Caldwell, Sr.

Assistant Examiner—Alvin Oberley

Attorney, Agent, or Firm—Morland C. Fischer

[57] ABSTRACT

A control that uses movement to position an image on a screen for use with means for detecting the movement and a microprocessor that interprets the movement detected and means for displaying an image on a screen, comprising a body and a bar having a bar axis coupled to the body so that the bar is rotatable with respect to the body about the bar axis and is slidable with respect to the body in a direction parallel to the bar axis thereby permitting movement of the bar with respect to the body which is the movement that is used to position an image on a screen.

12 Claims, 1 Drawing Sheet

